

HD-SDI HYbrid Series

Model Number AHD8240HYB

- Features
- HD-SDI Analog DVR
 - 8 Channel inputs
 - HDMI Monitor output @ 1080P*
 - VGA Monitor
 - 1080P Images
 - H.264 Compression
 - Supports I Pad and I Phone
 - HD over Coax
 - USB Backup
 - Rack Mount



Mouse Support



Specifications

| | |
|---------------------|---|
| Channels | 8 Analog Camera Inputs |
| Audio | 8 Channel |
| Display fps | 240fps |
| Resolution | 720P and 1080P |
| Record fps | 240fps @ 1080P image quality |
| Network | RJ45 Ethernet Connection |
| Operating System | Linux |
| Warranty | 2 year manufacturing |
| Power | 120v AC UPS recommended |
| Monitor | HDMI, VGA |
| Input option | 75ohm, BNC |
| HDD Capacity | Maximum of 6 Terabytes |
| Remote View | IE, I Pad, I Phone, Droid, Windows XP, Vista, 7, 3GPP |
| Case Options | Full Size Rack Mount Chassis |
| Camera type | HD-SDI |
| Storage | 2000, 3000, 6000 GB HDD |
| Bit-rate | Variable |
| DDNS | <i>One Touch DNS server support with auto-configure</i> |
| License Plate | Under 15 MPH with lane control, correct camera and low camera angle |
| Central Monitoring | CMS platform |
| Motion Detection | Yes |
| Record Triggers | Motion/Alarm/Sensor/Continuous/Schedule |
| Data Lifetime | Programmable Storage History |
| Data Capture | N/A |
| Remote Notification | Email |
| Display options | 1,4,8 |

Recommendations

Today's video systems have made great strides forward in image resolution. The HD-SDI product line is one example of how technology has allowed us to offer superior image quality. This technology takes advantage of the existing infrastructure of a legacy analog system and allows an image quality solution of 2.2 megapixels or 1080P resolution. This is the highest available resolution on the market today to utilize conventional wiring of a legacy CCTV system. Expect superior image quality to any other analog video system you have experienced. This Video Recording appliance offers all the latest drivers and software applications to support I pad, I phone, Android and Central Monitoring needs. Due to its ability to dual stream we can support full 1080P resolution images on site while supporting remote live images at a lower resolution to work with today's existing Internet Service Providers. This is a stable, robust, high resolution, imaging appliance capable of supporting the most demanding video requirements for both Public and Private installations.