

Model
Features

Commercial Outdoor PTZ with Wall mount

1/4 Sony Super HAD 550/680TVL Day/Night

3.5~94.5mm lens Optical Zoom

27x Optical 12x Digital Zoom

Vandal Resistant Case IP67

Image Stabilization



Specifications

Image Device	¼ Sony Super HAD
Signal Format	NTSC
Picture Element	NTSC: 768 x 494-B/W
Horizontal Resolution	550/680TVL Day/Night
Sensitivity	Color 0.4 Lux/Black White 0.02 Lux ICR cut filter
Day/Night Mode	Auto, Day, Night, ICR filter
Scanning System	2:1 Interlaced
Synchronization	Internal Sync
S/N Ratio	50db (AGC off)
Auto Gain	Yes
White Balance	Auto
Electronic Shutter	1/60-1/100,000 sec
Protocol	Pelco P/D 9600-4800 (Auto Configure)
Video Out	75ohm BNC
Zoom	12x digital zoom/27x optical Zoom
Mirror	Yes
Gamma Ratio	0.45
Presets	127 (400 degrees/sec)
Patterns	4 (record time is up to 5 minutes)
Privacy	8 Zones
Heater/Blower	Yes
Dimensions	Housing 192x 193mm/7.6x7.6mm, Dome 150mm
Mount	Wall mount/Corner mount/Pole mount
Operating Temp	-30c-50c
Pan/Tilt	360 degrees continuous/90 degrees
Image Stabilization	On/Off
Power	24vAC 60watts

Recommendations

This is a highly flexible Pan, Tilt, Zoom, camera with long range zoom and image stabilization for steady pictures even at full zoom. Expect years of service from long life internals and IP 67 weather rating. For large high traffic areas Pan, Tilt, Zoom, cameras are excellent choices.

Accessories:

