

Model: 22X PTZ Commercial Hi Speed Dome

- Features:
- 1/4 Sony 480TVL
  - Heater/Blower
  - Dozens of Protocols
  - Includes Wall Mount and Power supply
  - Tours/Patterns/Cruises



Specifications:

Part No.	GV8271
Pick up Device	1/4 Sony CCD
Signal Format	Pal/NTSC
Picture Element	Pal: 752H x 582V NTSC: 768H x 494V
Horizontal Resolution	480TVL
Sensitivity	.01 lux w/no IR
Infrared LED	IR cut filter
Scanning System	2:1 Interlaced
Synchronization	Internal sync
S/N Ratio	50db (AGC off)
Auto Gain	Auto
White Balance	Auto
Electronic Shutter	1/50~1/100,000 sec
Back Light Comp	Auto
Video Out	1 Vp-p 75ohm composite, BNCx1
Pan Speed	.0~360/sec
Tilt Speed	.0~90/sec
Preset	220
Lens	22X optical 10x digital
Programs	Auto-cruise/Tour/Pattern
Power Supply	24v DC (+/- 2%)
Power Consumption	1.25ma (power supply included)
Gray mask Zones	8 global zones
Alarm	7 Alarm in/2 Alarm out
Weather Resistance	IP66
Operating Temperature	-20C to 50C RH 85%

Recommendations:

PTZ's are a great solution for areas where multiple areas of concern exist and they cannot be properly covered with the use of one wide angle camera and it makes no sense to install 10's of cameras to cover all the areas of concern. With patterns/tours and cruises this camera can cover very large areas with great detail by programming the camera to move from one area to another similar to a guard on tour. PTZ's have been great solutions for years.

Accessories:

This camera can be ordered as a wall mount ceiling mount or an optional corner or pole mount is also available.