

Model: 10X PTZ Commercial Indoor Hi Speed Dome

- Features:
- 1/4 Sony 500 TVL
 - Wall/Ceiling mounts
 - Dozens of Protocols
 - Great Picture with 500TVL
 - Tours/Patterns/Cruises



Specifications:

Part No.	H210
Pick up Device	1/4 Sony CCD
Signal Format	Pal/NTSC
Picture Element	Pal: 752H x 582V NTSC: 768H x 494V
Horizontal Resolution	500TVL
Sensitivity	.07 lux color/0.02 b/w mode
Infrared LED	N/A
Scanning System	2:1 Interlaced
Synchronization	Internal sync
S/N Ratio	50db (AGC off)
Auto Gain	Auto
White Balance	Auto
Electronic Shutter	Shutter speed x 128 -1/120,000 sec
Back Light Comp	Auto
Video Out	1 Vp-p 75ohm composite, BNCx1
Pan Speed	.05~360/sec
Tilt Speed	.1~180/sec
Preset	127
Lens	F= 3.8~38mm
Programs	Auto-cruise/Tour/Pattern
Power Supply	12v DC (+/- 2%)
Power Consumption	1.25ma (power supply included)
Protocol	Pelco P-D
Alarm	4 Alarm in
Weather Resistance	IP55
Operating Temperature	-10C to 50C RH 85%

Recommendations:

360 degree endless pan, 180degree tilt, auto flip, 127 presets w/camera label, 4 patterns, 1200 commands, pattern swing 1-180/sec, 8 groups (20 action entities per group) Other functions auto flip, auto parking, power up action. As always it's a good idea to power your PTZ's as close to the camera as possible for a long healthy life.

Accessories:

Includes power supply and wall mount.