

Model: Pan and Tilt Economy Dome

- Features:
- 1/4 Sony 480TVL
 - Wall/Ceiling mounts
 - Multiple protocols (inc. Pelco)
 - Great Picture with 480TVL
 - Manual 4-9mm vari-focal lens



Specifications:

Part No.	H210
Pick up Device	1/4 Sony CCD
Signal Format	Pal/NTSC
Picture Element	Pal: 752H x 582V NTSC: 768H x 494V
Horizontal Resolution	480TVL
Sensitivity	.01 lux w/no IR
Infrared LED	N/A
Scanning System	2:1 Interlaced
Synchronization	Internal sync
S/N Ratio	50db (AGC off)
Auto Gain	Auto
White Balance	Auto
Electronic Shutter	1/50~1/100,000 sec
Back Light Comp	Auto
Video Out	1 Vp-p 75ohm composite, BNCx1
Pan Speed	.0~12/sec
Tilt Speed	.0~12/sec
Preset	32
Lens	Manual 4-9mm vari-focal
Programs	N/A
Power Supply	12v DC (+/- 2%)
Power Consumption	1 Amp (power supply included)
Protocol	Multiple including Pelco
Alarm	N/A
Weather Resistance	IP55
Operating Temperature	-10C to 50C RH 85%

Recommendations:

PTZ's are a great solution for areas where multiple areas of concern exist and they cannot be properly covered with the use of one wide angle camera and it makes no sense to install 10's of cameras to cover all the areas of concern. This is a camera that not only offers your customer hands on control of cameras field of view, but also delivers it at an amazing value. This camera is great for mechanical shops, large storage areas, or general view applications. This camera can also be installed outdoors.

Accessories:

This camera comes with wall mount as pictures as well as ceiling mount by removing camera from wall mount and installing flush to any ceiling that will support weight of camera. We do not recommend installing on drop ceiling without additional support brackets.