

Model
Features

NB-1000K
1/3 Sony Super Had II CCD 56TVL
CS Mount Lens
0.0002 Lux
Dual Voltage 12vDC/24vAC
On screen menu



Lens not included

Specifications

Image Device	1/3 Sony Super HAD II CCD
Signal Format	Pal/NTSC
Picture Element	Pal:752 x 582 NTSC: 768 x 494
Horizontal Resolution	560 TVL Color/600 TVL B/W
Sensitivity	0.0002 Lux at F1.2(Sens up x 256)
Infrared LED	N/A
Scanning System	2:1 Interlaced
Synchronization	Internal Sync
S/N Ratio	48db (AGC off)
Auto Gain	On/Off (0-255)
White Balance	ATW/AWB/Fixed/Manual
Electronic Shutter	Fixed or Manual 1/60-1/100,000 sec
Back Light Comp	On/Off (64 grid area)
Video Out	75ohm
Audio Out	N/A
Mirror	On/Off
Gamma Ratio	0.45 (0.05~1.00)
Lens	Manual or Auto Iris lens control
Humidity	85% Relative
Power Supply	12v DC/24vAC (+/- 10%)
Power Consumption	150ma@12vDC/70ma@24vAC
Dimensions	110mm x 54mm x 58mm
Day/Night	Auto/B&W/Color
Operating Temp	-20c-55c
On Screen Menu	Yes Full Menu
Adjustments	Contrast/Sharpness/CB-Gain/CR-Gain

Recommendations

This is an excellent camera to use when mounting to metal buildings. Mount this camera in an environmental enclosure and eliminate any opportunity for transient voltage to leak into the camera image. Universal mounts available as well as enclosures with and without heater/blower combo

Accessories: