

Model
Features

Mini Dome
1/3 CMOS 550 TVL
Light weight Case
2 Axis bracket
White Base
3.6 mm IR Board lens



Specifications

| | |
|-----------------------|----------------------------|
| Image Device | 1/3 CMOS |
| Signal Format | Pal/NTSC |
| Picture Element | NTSC: 768 x 494 |
| Horizontal Resolution | 550 TVL |
| Sensitivity | 0.1 lux Color |
| Infrared LED | N/A |
| Scanning System | 2:1 Interlaced |
| Synchronization | Internal Sync |
| S/N Ratio | 50db |
| Auto Gain | Auto |
| White Balance | Auto |
| Electronic Shutter | 1/60-1/120,000 sec |
| Back Light Comp | Yes |
| Video Out | 75ohm |
| Audio Out | N/A |
| Mirror | N/A |
| Gamma Ratio | 0.45 |
| Lens | 3.6 mm Board Lens |
| Humidity | 95% Relative |
| Power Supply | 12v DC (+/- 10%) |
| Power Consumption | 50ma@12vDC Max |
| Dimensions | 96mm x 70mm |
| Weather Resistance | IP 55 |
| Operating Temp | -10c-+50c Deg C.RH 95% Max |
| | |
| | |

Recommendations

Use this camera indoors. Lightweight mount is perfect for suspended ceiling installations. The 550tvl CMOS processor provides for excellent image quality and detail.

Accessories: