

Model: ND2100HVE

- Features:
- 1/3 Sony 960 Exview HAD CCD 2
  - Color: 650TVL, B/W 700TVL
  - 3 Axis Bracket
  - 2D-DNR, BLC, HLC
  - Multi Language OSD, Motion Detection
  - Picture Quality Adjustment
  - ATR Digital Powerful 128X WDR (53dB)
  - Min. Illumination: 0.01 Lux



Specifications:

Model	ND2100HVE
Pick up Device	1/3 Sony 960H Exview HAD CCD2
Signal Format	Pal/NTSC
Picture Element	Pal: 752H x 582V NTSC: 768H x 494V
Horizontal Resolution	650 TVL : Color / 700 TVL B/W
Sensitivity	0.01 Color
Infrared LED	N/A
Scanning System	2:1 Interlaced
Synchronization	Internal sync
S/N Ratio	Over 48db (AGC off)
Auto Gain	Auto
White Balance	Auto
Electronic Shutter	1/60 -1/100,000 sec / 1/50 – 1/100,00
Back Light Comp	Auto
Video Out	CVBS:1.0Vp-p 75ohm
Spot Monitor Out	Yes
Mirror	Yes
Gamma Ratio	0.45
Lens	2.8mm – 12mm DC Auto Iris Vari-focal Lens
Lens Mount	Auto Iris
Power Supply	12v DC / 24v AC (Dual Voltage)
Power Consumption	130mA
Dimensions	124.1mm Base x 100mm Dome x 102mm H
Net weight	300g
Weather Resistance	Non weather resistant
Operating Temperature	-20~+60 Deg C.RH 95% Max.

Recommendations:

Use this camera in any indoor location. Three way gimble allows for mounting on walls or ceilings. This is a very popular indoor dome. This is a popular camera for installers who like the on board spot out for use with the field monitor and additional flexibility with the onboard menu system (OSD Control). Composite case makes for a light weight unit to mount directly to drop ceilings.

Accessories:



Wall Mount