

Model
Features

NSO3D100A

- 1/3 Interline CCD
- High sensitivity, Low smear, Anti-bloom
- Light composite case
- 2 Way gimble
- 4mm interchangeable board lens



Specifications

Image Device	1/3 Interline CCD
Signal Format	Pal/NTSC
Picture Element	Pal:752 x 582 NTSC: 768 x 494
Horizontal Resolution	420 TVL
Sensitivity	0.1 lux F2.0
Infrared LED	N/A
Scanning System	2:1 Interlaced
Synchronization	Internal Sync
S/N Ratio	48db (AGC off)
Auto Gain	Auto
White Balance	Auto
Electronic Shutter	1/60-1/100,000 sec
Back Light Comp	Auto
Video Out	75ohm
Audio Out	N/A
Mirror	N/A
Gamma Ratio	0.45
Lens	4.3mm
Humidity	90% Relative
Power Supply	12v DC (+/- 10%)
Power Consumption	250ma@12vDC
Dimensions	110mm x 73mm
Weather Resistance	N/A
Operating Temp	-10c-50c

Recommendations

Use this camera in any indoor environment. Case is designed for ceiling mounting. Board lens can be changed to an alternative angle of view. This camera provides an excellent indoor image. For best results use in smaller rooms 10x15 or such.

Accessories: