

Model
Features

Mini PTZ with mount
1/4 Interline CCD 540 TVL
3.8-38mm lens Optical Zoom
12x Digital Zoom
Vandal Resistant Case 3.5"
High Speed, 360 degree/Sec



Specifications

Image Device	¼ Interline CCD
Signal Format	NTSC
Picture Element	NTSC: 640 x 494
Horizontal Resolution	540 TVL
Sensitivity	Color 0.7 Lux
Infrared LED	N/A
Scanning System	2:1 Interlaced
Synchronization	Internal Sync
S/N Ratio	46db (AGC off)
Auto Gain	Yes
White Balance	Auto
Electronic Shutter	1/60-1/100,000 sec
Protocol	Pelco P/D 9600-4800
Video Out	75ohm field monitor plug on board
Zoom	12x digital zoom/10x optical Zoom F1.2-3.8-33mm
Mirror	Yes
Gamma Ratio	0.45
Presets	127
Patterns	4
Power Supply	Included 12vDC
Heater/Blower	Yes
Dimensions	3.5"x 9"
Mount	Included for Ceiling Mount
Operating Temp	-20c-55c
Pan/Tilt	360/90 degrees continuous
On screen display	Yes
IR led filter	N/A

Recommendations

This PTZ is very popular for busy indoor areas that require flexible viewing. Pelco protocol makes this PTZ extremely versatile for integration with most every DVR built today. Expect crisp clean images with 540tvl resolution. If mounting outside do not place in direct rain.

Accessories: