

## PTZ Controller

Model # 40ZCONTROL

- Features
- 3-Axis Joystick Keyboard
  - Steel Frame Design
  - Setting up ID Address from 1 ~ 255 for Speed Dome Camera or Receiver
  - Control Pan/Tilt, Focus, Zoom, Iris and other parameter setup
  - LCD Menu, easy to operate
  - Camera Setup, Camera Address, Preset, Auto tour, Auto Scan.
  - Control Range: 1200m (RS485)
  - Controls up to 32 Dome Cameras

### Specifications

Signal System RS 485

Functions on Keyboard: PTZ Commands: CALL, PRESET, SHOT  
Camera Commands: WIDE/TELE , FAR/NEAR, CAM/ID, AUTO,  
OPEN/CLOSE

Other Functions: ON/OFF, LIVE/TAPE, F1, F2, F3, SEQ/MUL

Multiplexer view: FUNC/ Full Screen, 4x4, 2x2, 3x3, PIP

Numbers: 1~9 and Clear/Enter

Protocol: 1 Dipswitch set 1~8

Multi-protocol , Compatible with PELCO-D Protocol

2 sets of RS485 block connector

1 RJ11 RS485 Connector

Baud rate Communication: 2400BPS, 4800BPS, 9600BPS,  
19200BPS

Communication Distance: 1200m - 3936Ft

Power : DC12V 800mA

Weight: 2Kg - 4Lbs

Size: 380 x 165 x 80(mm)

